

C Z A R

PP-8000

POS Terminal Machine

Enhanced POS Solutions

Aluminum housing mechanism built for durability



#Key Features

- #Easy Maintenance Tools*
- #Easy Cable Management*
- #Water Splash Resistant*
- #Alloy Screen Panel Design*
- #Fanless Technology*

Aluminum Thermal Printer Stand [A8V2]

- #Designed for Space Saving Concept Store*
- #Durable Aluminum Mechanism*
- #Seiko Print Head & Cutter*
- #Front Loading Design*
- #Water Splash Resistant*



Product Specifications

Model	PP8100-H15S	PP8100-H25B	PP8300-H25S
CPU	Intel Celeron Bay Trail D J1900 Quad Core up to 2.4G (2M Cache Fanless)	Intel Celeron Bay Trail D J1900 Quad Core up to 2.4G (2M Cache Fanless)	Intel Core i3, i3-3110M Dual Core 2.4G 3MB Cache 24W
Chipset	Bay Trail DJ1900	Bay Trail DJ1900	i3-3110M+HM76
Memory	4GB DDR3 on board (up to 16GB)	4GB DDR3 on board (up to 16GB)	4GB DDR3 on board (up to 16GB)
HDD	2.5" SATA 64GB/128GB SSD	2.5" SATA 64GB/128GB SSD	2.5" SATA 64GB/128GB SSD
Interface/ Port	6xUSB / 3xCOM/ 1xLPT/ 1xVGA/ 1xPS2/ 2xAudio 1xRJ45 / 2x10/100/1000 Base-T		
Touch Monitor	15" Resistive Touch (1024x786) TRUE - FLAT SCREEN Brightness 250 cd/m2 Contrast 600:1 Response time 8ms	15" Projected Capacitive Touch (1024x786) TRUE - FLAT SCREEN Brightness 300 cd/m2 Contrast 600:1 Response time 5ms	
Dimension	360(W) X 300(L) X 51.99 (H) mm		
Operation Condition	Temperature: up to 40 degree Humidity: 10 to 80%		
Add On VFD-8000QR LCD-80K/104K/M2600 MSR-8000VU WIFI OS	20*2 lines VFD Customer Display 8" 10.4" LED 15" LED Monitor/ Touch Monitor Display MSR Card 1.2.3 Track Reader Wifi Module Window XP/7/8/10 POS Ready 2009 / 7 / 10 IOT		



POSMAC™

 www.posmac.my

All products, brands or companies are trademarks or registered trademarks of their respective companies
Product specifications are subject to change without prior notice.