



## COLOUR OF YOUR LIFE



### Compact. Reliable. Value

Compact size with reliable printhead and affordable value.

- 3" Direct Thermal POS Printer with Auto Cutter
- Compact Design for Small Counter Space
- High Resolution of up to 203 dpi
- USB+Serial Combo, Ethernet Interface
- Drop-in Paper Loading

Built with exceptional price/performance ratio in mind, it ensures best-in-class performance and durability.

## Printing

Printing method	Direct thermal
Print width	72mm
Column capacity	576 dots/line 512 dots/line
Printing speed	200mm/s
Interface	USB+Serial / Lan
Printing paper	79.5±0.5mm×φ80mm
Line spacing	3.75mm (Adjustable by commands)
Column number	80mm paper: Font A - 42 columns or 48 columns/Font B - 56 columns or 64 columns/ Chinese,traditional Chinese - 21 columns or 24 columns
Character size	ANK · Font A : 1.5×3.0mm (12×24 dots) Font B : 1.1×2.1mm (9×17 dots) Chinese,traditional Chinese:3.0×3.0mm (24×24 dots)

## Cutter

Auto cutter	Partial
-------------	---------

## Barcode Character

Code Page	PC347 ( Standard Europe ) · Katakana · PC850 ( Multilingual ) · PC860 ( Portuguese ) · PC863 ( Canadian-French ) · PC865 ( Nordic ) · West Europe · Greek · Hebrew · East Europe · Iran · WPC1252 · PC866 ( Cyrillic#2 ) · PC852 ( Latin2 ) · PC858 · IranII · Latvian · Arabic · PT151 ( 1251 )
Barcode types	UPC-A/UPC-E/JAN13 ( EAN13 ) /JAN8 ( EAN8 ) /CODE39/ITF/CODABAR/CODE93/CODE128

## Buffer

Input buffer	512K Bytes
NV Flash	256k bytes

## Power

Power adaptor	Input : AC 110V/220V, 50~60Hz
Power source	Output : DC 24V/2.5A
Cash drawer output	DC 24V/1A

## Physical characteristics

Weight	1.0KG
Dimensions	183.×140×141.5mm (D×W×H)

## Environmental Requirements

Work environment	Temperature (0~45) humidity(10~80%)
Storage environment	Temperature(-10~60℃) humidity(10~80%)

## Reliability MAX

Cutter life	1million cuts
Printer head life	100KM