



POSMAC PRINT

CP-Q3

80MM THERMAL PRINTER



#Key Features

#4MB Input Buffer Memory Avoid Order Missing

#100K Lifespan Printhead

#1 Million times Lifespan Cutter

#Multi IO Port

#Support QR & Chinese printing

#Support Win/Linux & OPOS

#2 Way Stand

#Wall Mount Ready

Designed for Hospitality Service



Food & Beverages POS



Retail & Mobile POS



Hospitality POS



Model	CP-Q3
Printing Method	Direct Thermal
Print Speed	260mm/S
Memory	Input Buffer 4MB NV flash buffer 256k
Paper width	79.5+-0.5mm 57.5+-0.5mm
Paper Diameter	80mm
Column capacity	576dots/line or 512 dots/line
Line space	3.75mm (changeable commands)
Character size	ANK, Font A: 12x24 dots Font B: 9x17 dots Chinese : 24x24 dots
Barcode	UPCA/UPCE/JAN13(EAN13)/JAN8(EAN8)/CODE39/ITF/CODEBAR/CODE 93/CODE128/ QR CODE/ PDF417
Code Page	PC347 (Standard Europe) PC850 (Multilingual) PC852 (Latin2) PC858 (Arabic)
Print Head	Japan Brand Lifespan 100,000 times
Auto Cutter	FULL/HALF Lifespan 1 million times
Interface/ Port	Serial + USB +LAN
Operation Condition	Temperature: up to 60 degrees Humidity: 10 to 80%
Drivers	Win 9X/ME/2000/XP/NT/VISTA, WIN 7/8/ 10 LINUX /OPOS
Command	Compatible with ECS/POS
Operation Condition	Temperature: up to 60 degrees Humidity: 10 to 80%
Add On	Wall Mount Auto Open Cover
Dimension Weight	185(L)*140(W)*134(H) mm 1.81kg