



2" THERMAL DIRECT LABEL
32bit RISC CPU
4MB FLASH MEMORY
MIRCOSD SLOT EXP

BP-525D THERMAL DIRECT BARCODE PRINTER	
Memory	4MB FLASH /8MB SDram
Printing Method	Direct Thermal Mechanism
Max Print	54mm (W) / 2286mm (L)
Printing Speed	50mm, 76mm, 100mm, 127mm (2, 3, 4, 5 ips) 50mm, 76mm, (2, 3 ips) selectable with peel off function
Interface	USB+RS232 / USB+LAN
Support Driver	Application Software: Bar Code Symbologies Windows Driver: For Windows 95, 98, NT4.0, 2000, XP. Software: Bar Tender
Support Printing	1D/ 2D QR CODE / Multiple Interface Language
Enclosure / Dimension	Material: Double-walled Plastic Operation Panel: LED (3 colors, Error, On line, Clearing data and Downloading data), Power Switch, Feed button Dimension: 209mm x 109mm x 171mm (8.23" x 4.29" x 6.73") Label roll capacity: 127mm (5") OD, 1" core Others: With wall mounting hole at the bottom cover
Media Support	UPC-E, EAN and UPC 2(5) digits add-on, MSI, PLESSEY, POSTNET, China Post, RSS-14, Code 11 Media core diameter: 25.4~38mm Label length: 10~2,286mm (0.39"~90") Peel off mode: 25.4~152.4mm (1"~6") Cutter mode: 25.4~2,286mm (1"~90")

