

Q1

**COMPACT DESIGN,
RELIABLE PERFORMANCE**



#Key Features

- 3" Direct Thermal POS Printer with Auto Cutter
 - Compact Design for Small Counter Space
 - Printing Speed up to 260mm/s
 - High Resolution of up to 203 dpi
 - Combo USB+Serial+Ethernet Interface
 - Drop-in Paper Loading



Designed for Hospitality Service



Food & Beverages POS



Retail & Mobile POS



Hospitality POS

Product Specifications

Printing

Printing method	Direct thermal
Print width	72mm
Column capacity	576 dots/line 512 dots/line
Printing speed	260mm/s
Interface	USB+Serial+Lan
Printing paper	79.5±0.5mm×φ80mm
Line spacing	3.75mm (Adjustable by commands)
Column number	80mm paper: Font A - 42 columns or 48 columns/Font B - 56 columns or 64 columns/ Chinese,traditional Chinese - 21 columns or 24 columns
Character size	ANK , Font A : 1.5×3.0mm (12×24 dots) Font B : 1.1×2.1mm (9×17 dots) Chinese,traditional Chinese:3.0×3.0mm (24×24 dots)

Cutter

Auto cutter	Partial
-------------	---------

Barcode Character

Code Page	PC347 (Standard Europe) 、Katakana 、PC850 (Multilingual) 、PC860 (Portuguese) 、 PC863 (Canadian-French) 、PC865 (Nordic) 、West Europe 、Greek 、Hebrew 、East Europe 、Iran 、WPC1252 、PC866 (Cyrillic#2) 、PC852 (Latin2) 、PC858 、IranII 、 Latvian 、Arabic 、PT151 (1251)
Barcode types	UPC-A/UPC-E/JAN13 (EAN13) /JAN8 (EAN8) /CODE39/ITF/CODABAR/CODE93/CODE128

Power

Power adaptor	Input : AC 110V/220V, 50~60Hz
Power source	Output : DC 24V/2.5A
Cash drawer output	DC 24V/1A

Physical characteristics

Weight	1.0KG
Dimensions	183.×140×141.5mm (D×W×H)

Environmental Requirements

Storage environment Temperature(-10~60℃) humidity(10~80%)

Reliability MAX

Cutter life	1million cuts
Printer head life	100KM



www.posmac.my

Distribute by SurfsTeK Innovation Sdn Bhd (1188201-U) A Company of TechnoDex Berhad
All products, brands or companies are trademarks or registered trademarks of their respective companies
Product specifications are subject to change without prior notice.